



- Hybrid AHD DVR
- 8-channel
- AHD/TVI/CVI/CVBS/IP support
- 5.0Mp AHD support
- 1xSATA (max. 8Tb)
- ONVIF 2.4 protocol support
- Support mobile monitoring: iOS & Android
- Ability to work with Partizan Cloud Storage
- Remote access to the device with Partizan MAC

Your manual is here:
<http://manuals.partizan.global>



Partizan software:
<http://apps.partizan.global>



System		
Model		ADM-88V
Version		FullHD v5.1
Maximum connected cameras, pcs.		8
Operating system		Embedded Linux
Simultaneous multi-channel real-time recording		+
Playback		+
Network operation		+
USB backup		+
Operation modes		AHD/TVI/CVI/CVBS/IP
Record		
Record, channels x resolution @ fps	AHD	8x5.0M-N@15, 8xAHD-H@18, 8xAHD-N@25
	AHD + IP	8xAHD-H@18+8x2.0Mp@18; 4xAHD-H@25+4x2.0Mp@25
	IP	16x2.0Mp@18; 4x5.0Mp@15; 4x3.0Mp@18
Record storage, HDD*/network		+/+
Video compression		H.264 (HighProfile)/H.265
Space occupation for 25 fps/1 channel (per day)	Video	~80Gb(1080p), ~46Gb(960p), ~34Gb(720p), ~30Gb(960H), ~20Gb(D1)
	Audio	0.69Gb
*Please note, HDD is not included in the kit!		
Playback		
Playback archive records, channels x resolution @ fps	AHD	4x5.0M-N@15, 4xAHD-H@18, 8xAHD-N@25
	AHD + IP	2xAHD-H@18/2x2.0Mp@18; 4xAHD-H@25/4x2.0Mp@25
	IP	2x5.0Mp@15, 4x3.0Mp@18, 4x2.0Mp@18
Backup mode, network/USB		+/+
Preview screen		1/4/8
Record mode	Manual	+
	Alarm	+
	Motion Detection	+
	Schedule	+
Audio		
Audio compression		G.711A
Two-way audio		+
Network		
Network Interface		RJ-45 (10/100Base-T)
Network functions		Partizan MAC protocol/DDNS/IPFilter/Email/NTP/UPNP/FTP/RTSP
Languages supported		English, Russian, Arabic, French, Polish, Romanian, Hungarian, Italian, Czech
Default IP address		DHCP (Auto)
Default username		admin
Default password		admin
HTTP port		80
RTSP port		554
RTSP string		rtsp://192.168.1.10:554/user=admin&password=admin&channel=1&stream=0.sdp?
Control port		34567
Configuration software		Partizan (Setup Tool), Partizan Device Manager
Monitoring program		Partizan
Mobile software (support)		Partizan
Protocol integration		Partizan SDK, ONVIF 2.4+ (Profile S)
Interface		
Display quality		1920x1080; 1440x900; 1280x1024; 1280x720; 1024x768
Video	Inputs	8ch BNC
	Outputs	1ch VGA, 1ch HDMI
Audio	Inputs	1ch RCA
	Outputs	1ch RCA
Alarm	Inputs	-
	Outputs	-
PTZ control, port/protocol support		-
USB		2xUSB2.0
Internal SATA, pcs x max.Tb		1x8
External SATA, pcs x max.Tb		-
External eSATA, pcs x max.Tb		-
Dimensions		
Size, mm		255x236x44
Weight, g		900
Common		
Accessories	Optical mouse	+
	Power adapter	+
	IR remote	+
Power supply	DC12V, A	2.0
	PoE/Class	-
Housing material, plastic/metal		-/+
Front material, plastic/metal		+/-
Operating temperature, °C		0 - +55
Warranty, years		3

*Note: the functions, interface, component parts and the working sequence of the device are subject to alteration without prior notice from the manufacturer due to updates of the device itself as well as its software